



amethyst

A50-RIG



FEATURES

- Designed for Rigid Applications
- Developed for LED and Mercury Vapour UV Lamps
- Superior Media Adhesion
- Supported by NUtec Digital's Ink Delivery System Warranty

OVERVIEW

Amethyst A50-RIG is a premium quality rigid UV ink, with superior media adhesion qualities, designed for rigid applications and is suitable for LED as well as Mercury Vapour UV lamps.

The Amethyst A50-RIG is suitable for use with or without primer, on a large variety of rigid substrates, including: Polycarbonate, Melamine, Fluted Polypropylene as well as Decorative Applications on Glass, Acrylic and Ceramics.

This formulation is designed for compatibility across a broad range of print head types and features a superior colour gamut for bright, vivid images.

Provided the inks are used in regular applications, using suitable substrates, the printed images will last for up to 24 months.

PRINT HEAD COMPATIBILITY	Fujifilm Dimatix {Polaris PQ-512/(15 & 35pl), Galaxy JA 256/(30, 50 & 80pl), SE 128 (30pl), SM 128 (50pl), SL 128 (80pl), Nova JA 256/80}; Konica Minolta {KM512 14pl, KM1024 14pl}; Xaar {501 GS6, GS8, GS12 U 8-40pl, 128 40pl, 1001, 1002, 1003}; ToshibaTec {CE2, CA3, CE4 (6-90pl) and CA4 (6-42pl)}; Ricoh {MH1801/1901 Gen3-E1, MH1603/1803/1903 Gen3-E3, MH2620/2820 Gen4}; Seiko {508GS 12pl}
PACKAGING CONFIGURATIONS	1L, 2.5L Bottles
COLOURS AND SHELF LIFE	CMYKlCm 15 months. Varnish and White - 12 months
SHIPPING AND STORAGE INFORMATION	Storage & transit temperatures: +5°C to +35°C Store in a cool, dry area, not directly on the floor and away from direct sunlight
OPERATING SPECIFICATIONS	Temperature: +19°C to +28°C Relative Humidity: 30% to 80% Non-condensing

Ref.no. NU A50-RIG v1. All trademarks recognised. E&OE.