



nucoat

# NU-clear



## FEATURES

NUcoat NU-clear is a gloss UV stable single component water based clear coat system which incorporates unique self-cross linking chemistry that improves the chemical and scratch resistance of the product.

## OVERVIEW

NUcoat NU-clear is compatible with most UV cured and solvent based inks with a very wide media compatibility. It adheres well to PVC and many other rigid substrates.

NUcoat NU-clear has low blush or colour shift once applied to printed images and has good flow and levelling properties. It is possible to apply a second coat of NUcoat NU-clear over the first coat, once it has dried.

NUcoat NU-clear is ideally suited for use on self-adhesive vinyl, flexible, as well as certain rigid substrates requiring additional durability, as well as scuff and chemical resistance. For optimum results, ensure a dried film thickness of approximately 20 microns, which will result in an approximate coverage of 20 square meters per litre.

DRYING TIME	<p>PAD APPLICATOR: When using IR curing - 3 to 10 minutes</p> <p>AIR DRYING: 1 to 2 hours at +23 C and 50% relative humidity</p> <p>LIQUID LAMINATOR: Follow the manufacturers settings and instructions</p>
CLEANING INSTRUCTIONS	Use water and a mild soap solution
SHELF LIFE	12 months
SHIPPING AND STORAGE INFORMATION	<p>Storage &amp; transit temperatures: +10°C to +30°C</p> <p>Store in a cool, dry area, not directly on the floor and away from direct sunlight</p> <p>Non-hazardous cargo, not classified as flammable</p>
OPERATING SPECIFICATIONS	Temperature: +19°C to +28°C

Ref.no. NU NU-clear v1. All trademarks recognised. E&OE.