

# Printer

Solvent

innovative print systems 

# SIGNRACER



Technical features	Signracer 138+	Signracer 162+	Signracer 163x
Maximum Media Width	1371 mm		1625 mm
Maximum Printing Width	1361 mm		1615 mm
Media Thickness	Head height 1.5 / 2.5 mm		Head height 0,3 / 1.3 / 2.8 mm
Production Speed Ranges	5.9 / 7.9 / 11.8 / 28 m <sup>2</sup> /h	7.5 / 10.0 / 14.5 / 29 m <sup>2</sup> /h	10 / 15 / 20 / 29 / 36 m <sup>2</sup> /h
Top Engine Speed	28 m <sup>2</sup> /h	29 m <sup>2</sup> /h	48 m <sup>2</sup> /h [360 x 720]
Ink	Emerald E10-XP-ECO (C, M, Y, K) – cartridges 440 ml, Xi-rated Emerald E12-ERP (C, M, Y, K) – cartridges 440 ml, Xi-rated		
Head / Nozzle Configuration	180 nozzles x 8 lines = 1440 nozzles (1 print head)		180 nozzles x 8 lines = 1440 nozzles (2 print heads)
Print Resolutions	540 x 720 dpi, 720 x 720 dpi, 720 x 1080 dpi, 1440 x 720 dpi, 1440 x 1440 dpi		
Dimensions (H x W x D)	1218 x 1916 x 685 mm	1261 x 2698 x 885 mm	
Weight	82.3 kg	160 kg	221 kg
Power Consumption – Option	During printing: 500 W	During printing: 600 W	During printing: 650 W

Textile Printers: Signracer TD162 and TD262, Signracer TS162 and TS163



Fast drying TRUEeco ink